# Centerm

#### **Enterprise Thin Client**

**D620** 









#### **P**ROFILE

D620 is a highly efficient and powerful thin client for both local computing and Microsoft, Citrix, VMware virtual desktop environments. It has a zero-client style desktop with TOS or a Windows 10 IoT.

# **C**ERTIFIED BY







#### **F**EATURES

#### 01 Real 4K display

DP could support resolution rate up to 4K.

### **02** Multiple interfaces

For various applications and business demands


#### 03 Trusted Platform Module

Giving businesses a layer of protection for data from penetration.


#### 04 Multiple VDI protocol supported

Widely supports Citrix ICA/HDX, VMware PCoIP and Microsoft RDP.

#### CONNECTIVITY



- 1. Power Button
- 2. USB 3.0 Port
- 3. Mic-in
- 4. Line-out
- 5. DC 12V Input
- 6. PS/2 Keyboard



- 7. PS/2 Mouse
- 8. Serial Port
- 9. Parallel Port
- 10. DP port
- 11. RJ-45
- 12. USB 2.0 port
- 13. Kensington Lock Slot

# **S**PECIFICATION

Processor	Intel Celeron Quad Core 2.0 GHz
Available Operating System	WIN 10 IOT / TOS <sup>1</sup>
Protocol Clients	Citrix receiver/ Microsoft Remote Desktop Client / Vmware™ Horizon View™ Client
Management	CDMS <sup>2</sup>
RAM (DDR4)	4GB up to 16GB
Storage (SSD)	128GB m.2 NAND SSD Storage up to 512GB
Display	2 x DP
Resolution	3840x2160@60Hz (DP) <sup>3</sup>
LAN	x 1 (10/100/1000Mbps,RJ45)
USB 2.0	x 6
USB 3.0	x 2
Serial Port	x 1 (extensible to 4 via cable)
Parallel Port	x 1
PS/2 Port	x 2
Audio	Line-out x 1, Mic-in x 1
Dimension	206mm x 48mm x 215mm (stand excluded)/ 206mm x 83mm x223mm (stand included)
Net Weight	1.18 kg
Adapter	Worldwide auto-sensing 100-240V AC, 50/60 Hz, 12V/3A DC
TDP	< 10w
Mountings	Vertical feet standard
Security	Standard Kensington anti-theft keyhole
Cooling	Fan-less Convection
Operation Temperature	0°C to 40°C
Relative Humidity	30% to 90% non-condensing

# **O**ptional items

RAM (DDR4)	Available at 16GB
Storage	1 *mSATA, 1* M.2:
Networking	Additional 1 x (10/100/1000Mbps,RJ45) 1 x M.2 wireless module
Serial Port	Extensible to 6
Speaker	Internal
TPM module	2.0 Hardware

- 1. TOS: terminal operating system (Linux)
- 2. CDMS: Cinfin desktop management system
- Display performance depends on workloads and memory bandwidth.
  4Kx2K@60Hz supported only on 1 display at one time due to memory bandwidth limitation.

Learn more visit en.centerm.com







