

Thin Client

D640



Triple display



TPM



PROFILE

Equipped with the Intel Jasper lake 10w processor to ensure the sufficient performance as desktop-worthy thin client for education, enterprise and workstation. Citrix, VMware and RDP are supported by default, also enable to meet most case for cloud computing. Moreover, 2 DP and one full function USB type-C would dedicate to the multi-display scenario.

Regulatory Compliance



FEATUES

01 Real 4K display

2 DP and USB type-C support resolution rate up to 4K.

02 Multiple interfaces

USB 3.0 x 2, type-c x 1 and USB 2.0 x 6, can meet daily demand for USB connection, serial port and parallel port also would enrich peripherals utilizations.

03 Trusted Platform Module

Giving businesses a layer of protection for data from penetration.


04 Triple display supported

2 DP + Type C support 3 monitors display and work at the same time.

05 Dual 1000 Mbps network adaptor

Dual 1000 Mbps Ethernet ports bring a leisured internet suffering and a speeding data transmission

CONNECTIVITY



- 1. Power Button
- 2. USB 3.0 Port
- 3. Mic-in
- 4. Line-out
- 5. DC 12V Input
- 6. PS/2 Keyboard
- 7. PS/2 Mouse
- 8. Serial Port

- 9. Parallel Port
- 10. Type-C Port
- 11. Display Port
- 12. RJ45
- 13. USB 2.0 Port
- 14. RJ45 or Fiber(optional)
- 15. Kensington Lock Slot

SPECIFICATION

| | |
|----------------------------|---|
| Processor | Intel quad core 2.0 GHz |
| Available Operating System | WIN 10 IOT |
| Protocol Clients | Citrix workspace app/ Microsoft Remote Desktop Client / Vmware Horizon Client |
| Management | CDMS ¹ |
| RAM (DDR4) | 4GB |
| Storage (SSD) | 64GB mSATA |
| Display | 2 x DP |
| Resolution | 4096 x 2160 @ 60Hz (DP) , 4096* 2160 @60Hz (Type-C) |
| LAN | x 1 (10/100/1000Mbps,RJ45) |
| USB 2.0 | x 6 |
| USB 3.0 | x 2 |
| USB Type-C | x 1 |
| Serial Port | x 1 (extensible to 4 via cable) |
| Parallel Port | x 1 |
| PS/2 Port | x 2 |
| Audio | Line-out x 1 , Mic-in x 1 |
| Dimension | 206mm x 48mm x 215mm (stand excluded)/ 206mm x 83mm x 223mm (stand included) |
| Weight | 1.18kg |
| Adapter | Worldwide auto-sensing 100-240V AC, 50/60 Hz, 12V/3A DC |
| TDP | < 10w |
| Mountings | Vertical feet standard |
| Security | Standard Kensington anti-theft keyhole |
| Cooling | Fan-less Convection |
| Operation Temperature | 0°C to 40°C |
| Relative Humidity | 30% to 90% non-condensing |

Optional items

| | |
|--------------------------------------|---|
| RAM (DDR4) | Available at 16 GB |
| m.2 | x 1 SATA or PCIE, 2242 or 2280 x 1 (Wi-Fi) |
| Network | x 1 (10/100/1000M bps,RJ45) ² |
| Speaker | x 1 (Internal) |
| Storage | x 1 SATA |
| Fiber Ethernet Adapter. ² | x 1 |
| IC Card Reader | x 1 |
| TPM module | x 1 |

Learn more visit en.centerm.com

Follow us



1. CDMS: Cinfin Desktop Management System.

2. Other RJ45 port would be used when fiber optic is embedded-in