

Centerm
All-In-One

V640



PROFILE

V640 All-in-One client is the perfect replacement of PC plus monitor solution adopting high performance Intel 10nm Jasperlake processor with 21.5' screen and elegant design. Intel Celeron N5105 is a quad-core processor of the Jasper Lake series that is primarily intended for inexpensive desktops and massive official task.

FEATURES

➤ Simple deployment

With simplified setup, configuration and management. Centerm AIO thin client can be deployed right out-of-the-box.

➤ VDI Support

Supports Citrix, VMware and Microsoft virtualization solutions offer smooth user experience in the cloud computing condition and virtual workspace utilization.


➤ Secure

Windows 10 IoT Enterprise with Centerm added security features to hardening to limit attack surfaces and get OS restored from virus and malware quickly.

➤ Varied Peripherals

2 x USB3.0 ports, 5 x USB 2.0 ports, 1x multi-utilization type-c port, plus serial port and parallel port, adopting in the scenario of the heavy demands of the peripherals

CONNECTIVITY



SPECIFICATION

SYSTEM

| | |
|------------------|---|
| Processor | Intel quad core 2.0GHz |
| Operating System | WIN 10 IOT |
| Protocol Clients | Citrix workspace app/ Microsoft Remote Desktop Client / VMware Horizon Client |
| Management | CDMS ¹ |

MEMORY

| | |
|------------|-------------|
| RAM (DDR4) | 4 GB |
| Storage | 64 GB mSATA |

DISPLAY

| | |
|--------|------------------------------|
| Screen | 21.5" LVDS :1920 x1080@ 60Hz |
|--------|------------------------------|

NETWORK

| | |
|-----|---|
| LAN | x 1 (10/100/1000 Base-T Fast Ethernet, RJ-45) |
|-----|---|

I/O PERIPHERAL

| | |
|---------------|--------------------------------|
| USB 2.0 | x 5 (rear) |
| USB 3.0 | x 2 (side) |
| Serial Port | x1 (extensible to 4 via cable) |
| Parallel Port | x1 |

AUDIO

| | |
|------|-------------------|
| Port | 2-in-1 Audio port |
|------|-------------------|

DIMENSION

| | |
|--------|---|
| Device | 490mm x 361mm x 162mm (including stand) 490mm x 292mm x 51mm (without stand) |
| Weight | 3.85kg |

POWER

| | |
|---------|---|
| Adapter | Worldwide auto-sensing 100-240V AC, 50/60 Hz, 12V/5A DC |
| TDP | 10W |

MOUNTING

| | |
|----------|--|
| Stand | Vertical feet standard |
| Security | Standard Kensington anti-theft keyhole |

ENVIRONMENT

| | |
|-----------------------|---------------------------|
| Operation Temperature | 0°C to 40°C |
| Relative Humidity | 30% to 90% non-condensing |

1. CDMS: Cinfim Desktop Management System

OPTIONAL CONFIGURATION

| | |
|------------|---|
| RAM (DDR4) | Available at 16 GB |
| Storage | x 1 m.2 (2280) x 1 SATA |
| Network | x 1 (10/100/1000 Base-T Fast Ethernet, RJ-45) |
| Type-C | x 1 4096*2160@60Hz |
| DP | x 1 4096*2160@60Hz |
| Speaker | Internal |
| Wi-Fi | x1 m.2 |
| TPM | 2.0 |